




Dimensions



Model D



Model B & C



Model A is mounted in a 6x6x4 wiring box with screwed on cover

Output pulse can be DC, AC, or dry contact. Specify on order

All models operate on 115 volts 60 cycles. Output pulse can be D.C. by including a rectifier.

PRICES

Model A - - -	95.00
Model B - - -	122.50
Model C - - -	135.00
Model D - - -	160.00

Write for quantity discounts

Ordering Information

Specify Royson Bulletin 700 Quick Contact Timer
Give Model, Range, and state if rectifier is needed

ROYSON ENGINEERING COMPANY

HATBORO, PENNSYLVANIA • OSborne 5-2800

The timer packages described in this bulletin all have one characteristic in common. They all run continuously, producing a pulse, or short contact closure at regular intervals. They vary only in the degree of adjustability.

Model A - This model is fixed in both time interval and pulse length. See the table below for ranges. The pulse length is nominal and may vary 20 %

Model B - This model has a fixed time interval but an adjustable Pulse. The pulse length is continuously variable from zero to 1.5 or 12 seconds.

Model C - This model has an adjustable time interval but a fixed pulse. The time interval is continuously adjustable over its entire range. The standard ranges are listed below. The pulse lengths are nominal.

Model D - This model has both interval and pulse length adjustable. Both are continuously adjustable over their entire range.

STANDARD TIME RANGES

Fixed "OFF" time ranges - 1, 5, 15, 30, or 60 minutes

Fixed "ON" time, or pulse - 1/2, or 1 second

Adjustable "OFF" time - 1, 5, 15, 30, 60, or 120 minutes

Adjustable "ON" time, or pulse length - 1.5 or 12 seconds

Other ranges can be provided. Send your complete specifications.

additional details are given on the reverse side

ROYSON ENGINEERING COMPANY

HATBORO, PENNSYLVANIA • OSborne 5-2800